

TLDI

MD75C<sub>2</sub>



Exceed the European Union emission standards.



California C.A.R.B.  
three star rating  
for ultra-low emissions.

TLDI

## Specifications

**Type** TLDI (Two-Stroke Low-Pressure Direct Fuel Injection)

**Maximum output** KW (PS) 56 (75)

**Maximum operating range** r/min 5150-5850

**Fuel consumption at W.O.T** L/Hr (gal/Hr) 26 (6.9)

**Number of cylinder** 3

**Bore x Stroke** mm (in) 86x72.7 (3.39x2.86)

**Displacement** ml (Cu in) 1267 (77.3)

**Engine lubrication system** Auto Mixing (Electrical oil

**Starting system** pump) Electric starter

**Spark plug** NGK IZFR6Q

**Ignition timing** Electronically advanced

**Alternator output** 12V 490W 40A

**Engine oil** 2-Stroke Engine Oil

**Volume of engine oil** L (gal) 4 (1.06)

**Fuel tank capacity** L (gal) Option 25 (6.6)

**Speed control** Remote control

**Gear reduction ratio** 2.33 (12:28)

**Emission Compliance** EU & EPA & CARB 3-Star

TLDI

Specifications and descriptions are subject to change without notice.

## Standard & Optional Equipments


Type	EPTOL/UL
Electric Starter	●
Engine Stop Switch Lanyard	●*
Alternator	●
Rectifier	●
Power Trim & Tilt	●
Oil Auto Mixing	●
Transom	20/25
Propeller	○
Analog Tachometer	○
Analog Trim Meter	○
Remote Control Box	○
25L (6.6 Gal) Plastic Fuel Tank	○
Tool Kit	●
Spare Spark Plug	●
Owners Manual	●

TLDI

● Standard   ○ Optional  
 \* Equipped with the remote control box



**3-Cylinder**



**Direct Fuel Injection**



**Low Fuel Consumption**



**Alternator**



**Charging System**



**Thermostat**



**Trolling Speed Control**



**Power Trim & Tilt**



**Multifunctional Tachometer**



**Over-Heat Buzzer**



**High Solid Paint Coating**



**Tohatsu Onboard Communication System**