FOUR STROKE

MFS25C





Exceed the European Union emission standards.



California C.A.R.B three star rating for ultra-low emissions.

FOUR STROKE

Specifications

Туре	Four Stroke EFI		
Maximum output	KW (PS)	18.4 (25)	
Maximum operating range	r/min	5000-6000	
Fuel consumption at W.O.T	L/Hr (gal/Hr)	8.8 (2.32)	
Number of cylinder		3	
Bore x Stroke	mm (in)	61x60 (2.40x2.36)	
Displacement	ml (Cu in)	526 (32.09)	
Engine lubrication system		Trochoid pump	
Starting system		Manual or Electric starter	
Spark plug		NGK DCPR6E	
Ignition timing		Electronically advanced	
Alternator output		12V 180W 15A	
Engine oil		4-Stroke Engine Oil 1.8 (1.9) w/	
Engine oil capacity	L (qt)	Filter change	
Fuel tank capacity	L (gal)	25 (6.6)	
Speed control		Twist grip type or Remote control	
Gear reduction ratio		2.17 (12:26)	
Emission Compliance		EU & EPA & CARB 3-Star	

Specifications and descriptions are subject to change without notice.

Standard 9 Ont	ional Fa	uinmonta	
Standard & Opt	S/L	EPS/L	EPTS/L
Electric Starter	-	•	•
Manual Recoil Starter	•	•	•
Decompression Release	•	•	•
Engine Stop Switch Lanyard	•	•	•
Alternator	•	•	•
Rectifier	\circ	•	•
Gas Assist Tilt	-	-	-
Power Tilt	-	-	•
Transom	15/20	15/20	15/20
Propeller	•	•	•
Analog Tachometer	\circ	0	0
Analog Trim Meter	-	-	\circ
Remote Control Box	-	•	•
Multi Tiller Handle	\circ	0	0
25L (6.6 Gal) Plastic Fuel Tank	•	•	•
Tool Kit	•	•	•
Emergency Starter Rope	•	•	•
Spare Spark Plug	•	•	•
Owners Manual	•	•	•

StandardOptional



3-Cylinder



Battery-less Electronic Fuel Injection



Low Fuel Consumption



Alternator



Charging System (Electric Model)



Thermostat



Manual Start Back-Up



Throttle Friction



Front Shift Control



Simple Steering Friction Lever (Manual Tilt)



Power Tilt



Diagnostics



Over-Heat Buzzer



High Solid Paint Coating



Dual Water Intake



Multi Tiller Handle #014362AB and later models



Trolling Speed Control (MFS25/30)